

V-S Led-tukku Oy - LNFS



IP rate  IP67



Application

Building and sign outline lighting,
Cove lighting, Bathroom lighting, Boat

Feature

Top lighting and top bending
Dual-color silicone extrusion
UV and yellowish resistant
IP67 and salt-mist proof
Customized length is available

Dimensions & available lengths



Electrical & Output Data

Model No.	LNFS
Step length (mm/x LED)	38.5mm / 7LEDs
Number LED/m	182
Voltage (v)	24V
Color	3000K / 4000K
CRI/Ra	80
Beam Angle(°)	115
Power (w/m)	7.68
Lumen(lm/m)	451 @ Ra80 @ 3000K
FPC width (mm)	8
max.length (m)	5
IP rate	67
Installation	Mounting Clips / Aluminum Profiles

The electrical data provided on the each product pages are for reference only;
the data values are not guaranteed. Specification may be subject to change without announcement.

accessories



Aluminum Channel



AL Mounting Clips






End cap



Silicone grease



Aluminum Channel

Aluminum Channel, 950(L) * 14.5(W) * 9.5(H)mm




AL Mounting Clips

AL Mounting Clips, 25(L) * 14.5(W) * 9.5(H)mm




End Caps


outlet from side, outlet from end, outlet from bottom



outlet from side



outlet from end



outlet from bottom